SAFETY DATA SHEET

SECTION 1 PRODUCT and COMPANY INFORMATION

TRADE NAME: Castle® Endura™ PRODUCT TYPE: Heavy Duty Penetrating Grease

PRODUCT CODE: C1630

MANUFACTURED FOR: Castle Products, Inc.

424 St. Paul Street Rochester, NY 14605 (800) 876-0222

EMERGENCY (585) 275-3232

SECTION 2 HAZARDS IDENTIFICATION

Flammable aerosols Physical hazards Category 1 Health hazards Acute toxicity, inhalation Category 4 Serious eye damage/eye irritation Category 2A

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Causes serious eye irritation. Harmful if inhaled.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area.

Wear eye protection/face protection.

If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse Response

cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Storage

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment, Category 3

long-term hazard

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

COMPOSITION INFORMATION ON INGREDIENTS SECTION 3

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|--|--------------------------|------------|---------|
| Acetone | | 67-64-1 | 10 - 20 |
| Lubricating Oils (petroleum), C15-30, Hydrotreated Neutral Oil-based | | 72623-86-0 | 10 - 20 |

Product Code: C1630 Endura Page 1 of 11

| Chemical name | Common name and synonyms | CAS number | % |
|--|--------------------------|-------------|----------|
| Lubricating Oils (petroleum), C20-50, Hydrotreated Neutral Oil-based | | 72623-87-1 | 10 - 20 |
| Petrolatum | | 8009-03-8 | 10 - 20 |
| Propane | | 74-98-6 | 10 - 20 |
| Isobutane | | 75-28-5 | 2.5 - 10 |
| Heptane, branched, cyclic and linear | | 426260-76-6 | 1 - 2.5 |
| Naphtha (petroleum), Hydrotreated Light | | 64742-49-0 | 1 - 2.5 |
| Cyclohexane | | 110-82-7 | 0.1 - 1 |
| Other components below reportable | e levels | | 20 - 40 |

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

SECTION 4 FIRST AID MEASURES

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or Inhalation artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell. Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth. Ingestion Most important Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. symptoms/effects, acute and delayed Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim Indication of immediate under observation. Symptoms may be delayed. medical attention and special

treatment needed General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

SECTION 5 FIRE FIGHTING MEASURES

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions

Specific methods

General fire hazards

Alcohol resistant foam. Dry powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA,

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

Extremely flammable aerosol.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Product Code: C1630 Endura Page 2 of 11 Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 2 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational exposure limits

| Components | Type | Value | |
|----------------------------------|--------------|------------|--|
| Acetone (CAS 67-64-1) | PEL | 2400 mg/m3 | |
| | | 1000 ppm | |
| Cyclohexane (CAS 110-82-7) | PEL | 1050 mg/m3 | |
| | | 300 ppm | |
| Propane (CAS 74-98-6) | PEL | 1800 mg/m3 | |
| | | 1000 ppm | |
| US. ACGIH Threshold Limit Values | | | |
| Components | Туре | Value | |
| Acetone (CAS 67-64-1) | STEL | 500 ppm | |
| | TWA | 250 ppm | |
| Cyclohexane (CAS 110-82-7) | TWA | 100 ppm | |
| Isobutane (CAS 75-28-5) | STEL | 1000 ppm | |
| US. NIOSH: Pocket Guide to Chem | ical Hazards | | |
| Components | Type | Value | |
| Acetone (CAS 67-64-1) | TWA | 590 mg/m3 | |
| | | 250 ppm | |
| Cyclohexane (CAS 110-82-7) | TWA | 1050 mg/m3 | |
| , | | 300 ppm | |
| Isobutane (CAS 75-28-5) | TWA | 1900 mg/m3 | |
| | | 800 ppm | |
| Propane (CAS 74-98-6) | TWA | 1800 mg/m3 | |
| | | 1000 ppm | |

Endura Product Code: C1630 Page 3 of 11

Biological limit values

ACGIH Biological Exposure Indices

Components Value Determinant Specimen Sampling Time

Acetone (CAS 67-64-1) 25 mg/l Acetone

* - For sampling details, please see the source document.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Urine

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear suitable protective clothing.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

SECTION 9 PHYSICAL and CHEMICAL PROPERTIES

Appearance

Physical state Gas.
Form Aerosol.
Color Not available.
Odor Not available.
Odor threshold Not available.
pH Not available.
Melting point/freezing point Not available.

Initial boiling point and boiling

range

166.18 °F (74.55 °C) estimated

Flash point -156.0 °F (-104.4 °C) propellant estimated

Evaporation rate Not available. Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

0.8 % estimated

(%)

Flammability limit - upper

5.8 % estimated

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 488 °F (253.33 °C) estimated

Decomposition temperature Not available.

Endura Product Code: C1630 Page 4 of 11

Viscosity Not available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Specific gravity 0.313 estimated

SECTION 10 STABILITY and REACTIVITY DATA

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

Hazardous decomposition

products

No hazardous decomposition products are known.

SECTION 11 TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Harmful if inhaled.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision.

Information on toxicological effects

Acute toxicity Harmful if inhaled.

Components Species Test Results

Acetone (CAS 67-64-1)

<u>Acute</u> Dermal

LD50 Guinea pig > 7426 mg/kg, 24 Hours

> 9.4 ml/kg, 24 Hours

Rabbit > 7426 mg/kg, 24 Hours

> 9.4 ml/kg, 24 Hours

Inhalation

LC50 Rat 55700 ppm, 3 Hours

132 mg/l, 3 Hours

50.1 mg/l

Oral

LD50 Rat 5800 mg/kg

2.2 ml/kg

Cyclohexane (CAS 110-82-7)

Acute Dermal

D50

LD50 Rabbit > 2000 mg/kg

Inhalation

LC50 Rat > 32880 mg/m3, 4 Hours

> 5540 ppm, 4 Hours

Oral

LD50 Rabbit > 5000 mg/kg

Endura Product Code: C1630 Page 5 of 11

| | /kg |
|--|---------------|
| Isobutane (CAS 75-28-5) | |
| <u>Acute</u> | |
| Inhalation | |
| | 120 Minutes |
| 52 %, 120 l | Minutes |
| Rat 1355 mg/l | |
| Lubricating Oils (petroleum), C15-30, Hydrotreated Neutral Oil-based (CAS 72623-86-0) | |
| <u>Acute</u> | |
| Dermal | |
| LD50 Rabbit > 2000 mg/ | - |
| > 2000 mg/ | /kg, 24 Hours |
| Inhalation | |
| LC50 Rat 2.18 mg/l, 4 | 4 Hours |
| Oral | |
| LD50 Rat > 2000 mg/ | /kg |
| Lubricating Oils (petroleum), C20-50, Hydrotreated Neutral Oil-based (CAS 72623-87-1) | |
| <u>Acute</u> | |
| Dermal Dermal | a. |
| LD50 Rabbit > 2000 mg/ | _ |
| - | /kg, 24 Hours |
| Inhalation | |
| LC50 Rat 2.18 mg/l, 4 | 4 Hours |
| Oral | |
| LD50 Rat > 2000 mg/ | /kg |
| Naphtha (petroleum), Hydrotreated Light (CAS 64742-49-0) | |
| Acute | |
| Dermal LD50 Guinea pig; Rabbit > 9.4 ml/kg | 24 Hours |
| | |
| | /kg, 24 Hours |
| Inhalation LC50 Rat > 5000 mg/ | / 2 |
| · · | /m3, 4 Hours |
| > 4980 mg/ | |
| - | /m3, 4 Hours |
| > 4.96 mg/l | |
| 13700 ppm | n, 4 Hours |
| Oral | |
| LD50 Rat 4820 mg/kg | g |
| Petrolatum (CAS 8009-03-8) | |
| <u>Acute</u> | |
| Dermal Dermal | |
| | /kg, 24 Hours |
| - | /kg, 24 Hours |
| Oral D. F. Constant of the Con | п |
| LD50 Rat > 5000 mg/ | /kg |
| Propane (CAS 74-98-6) | |
| Acute Industrian | |
| Inhalation LC50 Mouse 1237 mg/l, | 120 Minutes |
| 1237 HIg/I, | 120 Millut03 |

Test Results Components **Species** 52 %, 120 Minutes Rat 1355 mg/l 658 mg/l/4h

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

Not classified.

single exposure

Specific target organ toxicity -

repeated exposure Aspiration hazard

Not classified.

Not likely, due to the form of the product.

SECTION 12 ECOLOGICAL INFORMATION

| Ecotoxicity | y Harmful to aquatic life with long lasting effects. | | |
|---------------------|--|---|------------------------------------|
| Components | | Species | Test Results |
| Acetone (CAS 67-64- | 1) | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | 21.6 - 23.9 mg/l, 48 hours |
| Fish | LC50 | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 4740 - 6330 mg/l, 96 hours |
| Cyclohexane (CAS 1 | 10-82-7) | | |
| Aquatic | | | |
| Fish | LC50 | Fathead minnow (Pimephales prom | elas) 23.03 - 42.07 mg/l, 96 hours |

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Acetone -0.24Cyclohexane 3.44 Isobutane 2.76 Propane 2.36

No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

Product Code: C1630 Endura Page 7 of 11

^{*} Estimates for product may be based on additional component data not shown.

SECTION 13 DISPOSAL CONSIDERATIONS

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

SECTION 14 TRANSPORT INFORMATION

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Special provisions N82
Packaging exceptions 306
Packaging non bulk None
Packaging bulk None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards No. ERG Code 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

Packaging Exceptions LTD QTY

IMDG

UN number UN1950 UN proper shipping name AEROSOLS

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Endura Product Code: C1630 Page 8 of 11

Environmental hazards

Marine pollutant No. EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Packaging Exceptions
Transport in bulk according to
Annex II of MARPOL 73/78 and

LTD QTY Not applicable.

the IBC Code

DOT



IATA; IMDG



SECTION 15 REGULATORY INFORMATION

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1) Listed. Cyclohexane (CAS 110-82-7) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical nameCAS number% by wt.Cyclohexane110-82-70.1 - 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Isobutane (CAS 75-28-5) Propane (CAS 74-98-6)

Safe Drinking Water Act Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and

Chemical Code Number

Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Acetone (CAS 67-64-1)

Isobutane (CAS 75-28-5)

Lubricating Oils (petroleum), C15-30, Hydrotreated Neutral Oil-based (CAS 72623-86-0) Lubricating Oils (petroleum), C20-50, Hydrotreated Neutral Oil-based (CAS 72623-87-1)

Naphtha (petroleum), Hydrotreated Light (CAS 64742-49-0)

Petrolatum (CAS 8009-03-8)

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)

Cyclohexane (CAS 110-82-7)

Isobutane (CAS 75-28-5)

Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)

Cyclohexane (CAS 110-82-7)

Isobutane (CAS 75-28-5)

Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)

Cyclohexane (CAS 110-82-7)

Isobutane (CAS 75-28-5)

Propane (CAS 74-98-6)

US. Rhode Island RTK

Acetone (CAS 67-64-1)

Cyclohexane (CAS 110-82-7)

Isobutane (CAS 75-28-5)

Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|----------------------|--|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | No |
| Canada | Domestic Substances List (DSL) | No |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | No |
| Europe | European Inventory of Existing Commercial Chemical | No |

Substances (EINECS)

Europe European List of Notified Chemical Substances (ELINCS) No

Country(s) or region Inventory name On inventory (yes/no)*

JapanInventory of Existing and New Chemical Substances (ENCS)NoKoreaExisting Chemicals List (ECL)NoNew ZealandNew Zealand InventoryNo

Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

SECTION 16 OTHER INFORMATION

Other: NA-Not Applicable, ND-Not Determined, NE-Not Established.

Disclaimer Terms and Conditions. This SDS is designed only as guidance for the products to which it applies. To the greatest extent permitted by applicable law, nothing contained herein creates any legal obligation including contractual obligations, expressed or implied warranties, including any warranties of merchantability or fitness for particular purpose; or confers any intellectual property rights, including rights to use trademarks or a license to use patents, issued or pending. The information contained herein is based on the manufacturer's own study and the work of others, and is subject to change at any time without further notice. There is no warranty, expressed or implied, as to the accuracy, completeness or adequacy of the information contained herein, and neither the provider nor the manufacturer (nor the agents, directors, officers, contractors or employees of either) are liable to any party for any damages of any nature, including direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnishing of any information in this SDS, or in any other way related (directly or indirectly) to this SDS. The receipt and use of this information constitutes consent to these terms and conditions.

Endura Product Code: C1630 Page 11 of 11