

# SAFETY DATA SHEET

## SECTION 1 PRODUCT and COMPANY INFORMATION

TRADE NAME: **Castle® Streak Proof™**

PRODUCT TYPE: Glass Cleaner  
PRODUCT CODE: C0603, C2003

MANUFACTURED FOR: Castle Products, Inc.  
424 St. Paul Street  
Rochester, NY 14605  
(800) 876-0222  
EMERGENCY (585) 275-3232

## SECTION 2 HAZARDS IDENTIFICATION

Physical hazards

Health hazards Not classified.

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Response Wash hands after handling.

Storage Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

## SECTION 3 COMPOSITION INFORMATION ON INGREDIENTS

Mixtures

| Chemical name                            | Common name and synonyms | CAS number | %        |
|--|--------------------------|------------|----------|
| 2-Butoxyethanol                          |                          | 111-76-2   | 2.5 - 10 |
| Isopropyl Alcohol                        |                          | 67-63-0    | 1 - 2.5  |
| Propane                                  |                          | 74-98-6    | 1 - 2.5  |
| Anhydrous Ammonia                        |                          | 7664-41-7  | 0.1 - 1  |
| Other components below reportable levels |                          |            | 90 - 100 |

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## SECTION 4 FIRST AID MEASURES

Inhalation If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

|  |  |
|--|--|
| Ingestion  | In the unlikely event of swallowing contact a physician or poison control center.                                |
| Most important symptoms/effects, acute and delayed                     | Direct contact with eyes may cause temporary irritation.   |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically.   |
| General information  | Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. |

### SECTION 5 FIRE FIGHTING MEASURES

|   |  |
|---|--|
| Suitable extinguishing media                                  | Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).  |
| Unsuitable extinguishing media                                | Do not use water jet as an extinguisher, as this will spread the fire.   |
| Specific hazards arising from the chemical                    | Contents under pressure. Pressurized container may explode when exposed to heat or flame.  |
| Special protective equipment and precautions for firefighters | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.   |
| Fire-fighting equipment/instructions                          | Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. |
| Specific methods  | Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.   |
| General fire hazards  | Extremely flammable aerosol.   |

### SECTION 6 ACCIDENTAL RELEASE MEASURES

|   |  |
|---|--|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.   |
| Methods and materials for containment and cleaning up               | Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.<br><br>Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. |
| Environmental precautions   | Avoid discharge into drains, water courses or onto the ground.   |

### SECTION 7 HANDLING AND STORAGE

|  |   |
|--|---|
| Precautions for safe handling                                | Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. |
| Conditions for safe storage, including any incompatibilities | Level 1 Aerosol.<br><br>Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).  |

**SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components                        | Type | Value      |
|-----------------------------------|------|------------|
| 2-Butoxyethanol (CAS 111-76-2)    | PEL  | 240 mg/m3  |
|                                   |      | 50 ppm     |
| Anhydrous Ammonia (CAS 7664-41-7) | PEL  | 35 mg/m3   |
|                                   |      | 50 ppm     |
| Isopropyl Alcohol (CAS 67-63-0)   | PEL  | 980 mg/m3  |
|                                   |      | 400 ppm    |
| Propane (CAS 74-98-6)             | PEL  | 1800 mg/m3 |
|                                   |      | 1000 ppm   |

US. ACGIH Threshold Limit Values

| Components                        | Type | Value   |
|-----------------------------------|------|---------|
| 2-Butoxyethanol (CAS 111-76-2)    | TWA  | 20 ppm  |
| Anhydrous Ammonia (CAS 7664-41-7) | STEL | 35 ppm  |
|                                   | TWA  | 25 ppm  |
| Isopropyl Alcohol (CAS 67-63-0)   | STEL | 400 ppm |
|                                   | TWA  | 200 ppm |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components                        | Type | Value      |
|-----------------------------------|------|------------|
| 2-Butoxyethanol (CAS 111-76-2)    | TWA  | 24 mg/m3   |
|                                   |      | 5 ppm      |
| Anhydrous Ammonia (CAS 7664-41-7) | STEL | 27 mg/m3   |
|                                   | TWA  | 35 ppm     |
|                                   |      | 18 mg/m3   |
|                                   |      | 25 ppm     |
| Isopropyl Alcohol (CAS 67-63-0)   | STEL | 1225 mg/m3 |
|                                   | TWA  | 500 ppm    |
|                                   |      | 980 mg/m3  |
|                                   |      | 400 ppm    |
| Propane (CAS 74-98-6)             | TWA  | 1800 mg/m3 |
|                                   |      | 1000 ppm   |

Biological limit values

ACGIH Biological Exposure Indices

| Components                      | Value    | Determinant                              | Specimen            | Sampling Time |
|---------------------------------|----------|--|---------------------|---------------|
| 2-Butoxyethanol (CAS 111-76-2)  | 200 mg/g | Butoxyacetic acid (BAA), with hydrolysis | Creatinine in urine | *             |
| Isopropyl Alcohol (CAS 67-63-0) | 40 mg/l  | Acetone                                  | Urine               | *             |

\* - For sampling details, please see the source document.

Exposure guidelines

- US - California OELs: Skin designation
  - 2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.
- US - Minnesota Haz Subs: Skin designation applies
  - 2-Butoxyethanol (CAS 111-76-2) Skin designation applies.
- US - Tennessee OELs: Skin designation
  - 2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

|   |   |
|---|---|
| Appropriate engineering controls                                      | Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. |
| Individual protection measures, such as personal protective equipment |   |
| Eye/face protection   | Wear safety glasses with side shields (or goggles).   |
| Hand protection   | Wear appropriate chemical resistant gloves.   |
| Skin protection   |   |
| Other   | Wear suitable protective clothing.  |
| Respiratory protection  | If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.   |
| Thermal hazards   | Wear appropriate thermal protective clothing, when necessary.   |
| General hygiene considerations  | When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.  |

|   |
|---|
| <b>SECTION 9 PHYSICAL and CHEMICAL PROPERTIES</b> |
|---|

|  |                                 |
|--|---------------------------------|
| Appearance                                   |                                 |
| Physical state                               | Liquid.                         |
| Form   | Aerosol.                        |
| Color  | Not available.                  |
| Odor   | Not available.                  |
| Odor threshold                               | Not available.                  |
| pH   | Not available.                  |
| Melting point/freezing point                 | Not available.                  |
| Initial boiling point and boiling range      | 195.27 °F (90.7 °C) estimated   |
| Flash point                                  | -245.2 °F (-154.0 °C) estimated |
| Evaporation rate                             | Not available.                  |
| Flammability (solid, gas)                    | Not available.                  |
| Upper/lower flammability or explosive limits |                                 |
| Flammability limit - lower (%)               | Not available.                  |
| Flammability limit - upper (%)               | Not available.                  |
| Explosive limit - lower (%)                  | Not available.                  |
| Explosive limit - upper (%)                  | Not available.                  |
| Vapor pressure                               | Not available.                  |
| Vapor density                                | Not available.                  |
| Relative density                             | Not available.                  |
| Solubility(ies)                              |                                 |
| Solubility (water)                           | Not available.                  |
| Partition coefficient (n-octanol/water)      | Not available.                  |
| Auto-ignition temperature                    | Not available.                  |
| Decomposition temperature                    | Not available.                  |
| Viscosity                                    | Not available.                  |
| Other information                            |                                 |
| Flammability class                           | Flammable IB estimated          |

Heat of combustion 3.29 kJ/g estimated  
 Specific gravity 0.926 estimated

**SECTION 10 STABILITY and REACTIVITY DATA**

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.  
 Chemical stability Material is stable under normal conditions.  
 Possibility of hazardous reactions Hazardous polymerization does not occur.  
 Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.  
 Incompatible materials Strong oxidizing agents.  
 Hazardous decomposition products No hazardous decomposition products are known.

**SECTION 11 TOXICOLOGICAL INFORMATION**

Information on likely routes of exposure

Ingestion Expected to be a low ingestion hazard.  
 Inhalation Prolonged inhalation may be harmful.  
 Skin contact 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

Eye contact Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

| Components                     | Species                           | Test Results                               |                  |
|--------------------------------|-----------------------------------|--|------------------|
| 2-Butoxyethanol (CAS 111-76-2) |                                   |  |                  |
| Acute<br>Dermal<br>LD50        | Guinea pig                        | 6411 mg/kg                                 |                  |
|                                |                                   | 230 ml/kg, 24 Hours                        |                  |
|                                |                                   | 7.3 ml/kg, 4 Days                          |                  |
|                                | Rabbit                            | 450 ml/kg, 24 Hours                        |                  |
|                                |                                   | 435 mg/kg, 24 Hours                        |                  |
|                                |                                   | 0.63 ml/kg                                 |                  |
| Rat                            | > 2000 mg/kg, 24 Hours            |  |                  |
|                                | Inhalation<br>LC50                | Mouse                                      | 750 ppm, 7 Hours |
|                                |                                   |  | Rabbit           |
| Rat                            |                                   |  | 450 ppm, 4 Hours |
| Oral<br>LD100<br>LD50          | Rabbit                            | 695 mg/kg                                  |                  |
|                                | Dog                               | > 695 mg/kg                                |                  |
|                                | Guinea pig                        | 1200 mg/kg                                 |                  |
|                                | Mouse                             | 1230 mg/kg                                 |                  |
|                                | Rat                               | 530 - 2800 mg/kg                           |                  |
|                                | Anhydrous Ammonia (CAS 7664-41-7) |  |                  |
| Acute<br>Inhalation<br>LC50    | Mouse                             | 4230 ppm, 1f <1L: Consumer Commodity Hours |                  |

| Components                      | Species | Test Results                                |
|---------------------------------|---------|---|
|                                 | Rat     | 7939 mg/m3                                  |
|                                 |         | 4000 ppm, If <1L: Consumer Commodity Hours  |
| Oral<br>LD50                    | Rat     | 350 mg/kg                                   |
| Isopropyl Alcohol (CAS 67-63-0) |         |   |
| Acute<br>Dermal<br>LD50         | Rabbit  | 16.4 ml/kg, 24 Hours                        |
| Inhalation<br>LC50              | Rat     | > 10000 ppm, 6 Hours                        |
| Oral<br>LD50                    | Rat     | 5.84 g/kg                                   |
| Propane (CAS 74-98-6)           |         |   |
| Acute<br>Inhalation<br>LC50     | Mouse   | 1237 mg/l, 120 Minutes<br>52 %, 120 Minutes |
|                                 | Rat     | 1355 mg/l<br>658 mg/l/4h                    |

\* Estimates for product may be based on additional component data not shown.

|  |   |
|--|---|
| Skin corrosion/irritation                                      | Prolonged skin contact may cause temporary irritation.  |
| Serious eye damage/eye irritation                              | Direct contact with eyes may cause temporary irritation.  |
| Respiratory or skin sensitization                              |   |
| Respiratory sensitization                                      | Not available.  |
| Skin sensitization   | This product is not expected to cause skin sensitization.   |
| Germ cell mutagenicity   | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.  |
| Carcinogenicity  | This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.   |
| IARC Monographs. Overall Evaluation of Carcinogenicity         |   |
| 2-Butoxyethanol (CAS 111-76-2)                                 | 3 Not classifiable as to carcinogenicity to humans.   |
| OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) |   |
| Not listed.  |   |
| Reproductive toxicity  | This product is not expected to cause reproductive or developmental effects.  |
| Specific target organ toxicity - single exposure               | Not classified.   |
| Specific target organ toxicity - repeated exposure             | Not classified.   |
| Aspiration hazard  | Not available.  |
| Chronic effects  | Prolonged inhalation may be harmful. May be harmful if absorbed through skin.<br><br>2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans. |

## SECTION 12 ECOLOGICAL INFORMATION

|             |  |
|-------------|--|
| Ecotoxicity | The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. |
|-------------|--|

| Components                        | Species | Test Results                                       |
|-----------------------------------|---------|--|
| 2-Butoxyethanol (CAS 111-76-2)    |         |  |
| Aquatic                           |         |  |
| Fish                              | LC50    | Inland silverside ( <i>Menidia beryllina</i> )     |
|                                   |         | 1250 mg/l, 96 hours                                |
| Anhydrous Ammonia (CAS 7664-41-7) |         |  |
| Aquatic                           |         |  |
| Fish                              | LC50    | Chinook salmon ( <i>Oncorhynchus tshawytscha</i> ) |
|                                   |         | 0.43 - 0.47 mg/l, 96 hours                         |
| Isopropyl Alcohol (CAS 67-63-0)   |         |  |
| Aquatic                           |         |  |
| Algae                             | IC50    | Algae  |
|                                   |         | 1000.0001 mg/L, 72 Hours                           |
| Crustacea                         | EC50    | Daphnia  |
|                                   |         | 13299 mg/L, 48 Hours                               |
| Fish                              | LC50    | Bluegill ( <i>Lepomis macrochirus</i> )            |
|                                   |         | > 1400 mg/l, 96 hours                              |

\* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

2-Butoxyethanol 0.83

Isopropyl Alcohol 0.05

Propane 2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### SECTION 13 DISPOSAL CONSIDERATIONS

|                                       |   |
|---------------------------------------|---|
| Disposal instructions                 | Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Local disposal regulations            | Dispose in accordance with all applicable regulations.  |
| Hazardous waste code                  | The waste code should be assigned in discussion between the user, the producer and the waste disposal company.  |
| Waste from residues / unused products | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).  |
| Contaminated packaging                | Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.              |

### SECTION 14 TRANSPORT INFORMATION

DOT

|                              |   |
|------------------------------|---|
| UN number                    | UN1950  |
| UN proper shipping name      | Aerosols, flammable, (each not exceeding 1 L capacity)                  |
| Transport hazard class(es)   |   |
| Class                        | 2.1   |
| Subsidiary risk              | -   |
| Label(s)                     | 2.1   |
| Packing group                | Not applicable.   |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Special provisions           | N82   |
| Packaging exceptions         | 306   |
| Packaging non bulk           | None  |
| Packaging bulk               | None  |

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

|                              |   |
|------------------------------|---|
| UN number                    | UN1950  |
| UN proper shipping name      | Aerosols, flammable   |
| Transport hazard class(es)   |   |
| Class                        | 2.1   |
| Subsidiary risk              | -   |
| Label(s)                     | 2.1   |
| Packing group                | Not applicable.   |
| Environmental hazards        | No.   |
| ERG Code                     | 10L   |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Other information            |   |
| Passenger and cargo aircraft | Allowed.  |
| Cargo aircraft only          | Allowed.  |
| Packaging Exceptions         | LTD QTY   |

IMDG

|  |   |
|--|---|
| UN number  | UN1950  |
| UN proper shipping name  | AEROSOLS  |
| Transport hazard class(es)   |   |
| Class  | 2.1   |
| Subsidiary risk  | -   |
| Label(s)   | 2.1   |
| Packing group  | Not applicable.   |
| Environmental hazards  |   |
| Marine pollutant   | No.   |
| EmS  | F-D, S-U  |
| Special precautions for user   | Read safety instructions, SDS and emergency procedures before handling. |
| Packaging Exceptions   | LTD QTY   |
| Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not applicable.   |

DOT



IATA; IMDG



|  |
|--|
| <b>SECTION 15 REGULATORY INFORMATION</b> |
|--|

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
 All components are on the U.S. EPA TSCA Inventory List.



TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Anhydrous Ammonia (CAS 7664-41-7) Listed.

SARA 304 Emergency release notification

Anhydrous Ammonia (CAS 7664-41-7) 100 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories  
 Immediate Hazard - No  
 Delayed Hazard - No  
 Fire Hazard - Yes  
 Pressure Hazard - No  
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance

| Chemical name     | CAS number | Reportable quantity | Threshold planning quantity | Threshold planning quantity, lower value | Threshold planning quantity, upper value |
|-------------------|------------|---------------------|-----------------------------|--|--|
| Anhydrous Ammonia | 7664-41-7  | 100                 | 500 lbs                     |  |  |

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

| Chemical name     | CAS number | % by wt. |
|-------------------|------------|----------|
| Anhydrous Ammonia | 7664-41-7  | 0.1 - 1  |

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Anhydrous Ammonia (CAS 7664-41-7)

Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

2-Butoxyethanol (CAS 111-76-2)

Anhydrous Ammonia (CAS 7664-41-7)

Isopropyl Alcohol (CAS 67-63-0)

Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

2-Butoxyethanol (CAS 111-76-2)

Anhydrous Ammonia (CAS 7664-41-7)

Isopropyl Alcohol (CAS 67-63-0)

Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

2-Butoxyethanol (CAS 111-76-2)

Anhydrous Ammonia (CAS 7664-41-7)

Isopropyl Alcohol (CAS 67-63-0)

Propane (CAS 74-98-6)

US. Rhode Island RTK

Anhydrous Ammonia (CAS 7664-41-7)

Isopropyl Alcohol (CAS 67-63-0)

Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

| Country(s) or region | Inventory name                                     | On inventory (yes/no)* |
|----------------------|--|------------------------|
| Australia            | Australian Inventory of Chemical Substances (AICS) | No                     |

| Country(s) or region        | Inventory name   | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Canada                      | Domestic Substances List (DSL)   | Yes                    |
| Canada                      | Non-Domestic Substances List (NDSL)                                    | No                     |
| China                       | Inventory of Existing Chemical Substances in China (IECSC)             | No                     |
| Europe                      | European Inventory of Existing Commercial Chemical Substances (EINECS) | No                     |
| Europe                      | European List of Notified Chemical Substances (ELINCS)                 | No                     |
| Japan                       | Inventory of Existing and New Chemical Substances (ENCS)               | No                     |
| Korea                       | Existing Chemicals List (ECL)  | No                     |
| New Zealand                 | New Zealand Inventory  | No                     |
| Philippines                 | Philippine Inventory of Chemicals and Chemical Substances (PICCS)      | No                     |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory                          | Yes                    |

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

### SECTION 16 OTHER INFORMATION

Other: NA-Not Applicable, ND-Not Determined, NE-Not Established.

Disclaimer Terms and Conditions. This SDS is designed only as guidance for the products to which it applies. To the greatest extent permitted by applicable law, nothing contained herein creates any legal obligation including contractual obligations, expressed or implied warranties, including any warranties of merchantability or fitness for particular purpose; or confers any intellectual property rights, including rights to use trademarks or a license to use patents, issued or pending. The information contained herein is based on the manufacturer's own study and the work of others, and is subject to change at any time without further notice. There is no warranty, expressed or implied, as to the accuracy, completeness or adequacy of the information contained herein, and neither the provider nor the manufacturer (nor the agents, directors, officers, contractors or employees of either) are liable to any party for any damages of any nature, including direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnishing of any information in this SDS, or in any other way related (directly or indirectly) to this SDS. The receipt and use of this information constitutes consent to these terms and conditions.

PREPARED: 6/9/94

UPDATED: 8/23/16

PRODUCT #: C0603, C2003