



Multi-Functional

**air
power** AP1 • AP2 • AP3
S E R I E S

Pneudraulic Blind Riveting Tools

AirPower Series pneudraulic blind riveting tools from Applifast are distinguished from other riveters by a streamlined, ergonomic design allowing easy set up and are constructed for continuous reliable use in demanding production conditions.

- ✓ Durable
- ✓ Ergonomic
- ✓ High-Speed
- ✓ User-Friendly
- ✓ Multi-Functional
- ✓ Cost Efficient

Experience the efficiency of airpower riveting

- ✓ The **multi-functional trigger** has low action for hours of comfortable use with one or two fingers.
- ✓ The integral **mandrel collection system** holds the rivet in the nose piece even when working 'face-down'.
- ✓ A **360° revolving air inlet** accommodates right or left handed users and can be rotated to access tight fastening locations in any position.
- ✓ A **composite body** reduces the weight of the tool and also prevents scratching to assembly materials.



Contact Applifast

Tel: 204 837 8361 • 1 800 563 1293
info@applifast.com

applifast.com



air power[®] AP1 • AP2 • AP3 S E R I E S

Pneudraulic Blind Riveting Tools

Multi-functional trigger controls the suction. When the trigger is pushed and shifted up, the suction is deactivated, when pushed and shifted down the suction is activated.

Designed with ergonomics in mind to increase endurance and personal comfort on the production line.

Tool suction holds a rivet in the tool while positioning even in face-down applications.

Tool hanger allows the riveter to be suspended from a tool balancer.

AP3
Z-13026001



360° Rotating air inlet enables a right handed or left handed operator to rivet in any position.

Articulating swivel air hose saves air consumption with inline shut-off slide valve.

Multi-functional mandrel collector is a simple and effective system contributing to a tidy production area.

Model	Capacity	Weight	Dimensions	Stroke	Pressure Required	Traction power (6 bar)	Nose Pieces Included
AirPower 1 Z-1100001	2.4 - 4.8 mm 3/32" - 3/16"	Al, St, Rv Al, St, Rv 1.447 Kg 3.191 Lbs.	272 mm x 264 mm x 99 mm 10.71" x 10.39" x 3.90"	17 mm 0.67"	5-7 Bar 80-100 PSI	7.3 kN (1,641 Lbf)	3.0 mm (1/8), 4.0 mm (5/32), 5.0 mm (3/16)
AirPower 2 Z-1200001	4.0 - 6.4 mm 5/32" - 1/4"	Al, St, Rv Al, St, Rv 1.848 Kg 4.075 Lbs.	272 mm x 275 mm x 120 mm 10.71" x 10.83" x 4.72"	21 mm 0.83"	5-7 Bar 80-100 PSI	12.5 kN (2,810 Lbf)	4.0 mm (5/32), 4.8/5.0 mm (3/16), 6.0 mm/6.4 mm (1/4)
AirPower 3 Z-13026001	4.8 - 6.4 mm 3/16" - 1/4"	Al, St, Rv Al, St, Rv 2.019 Kg 4.451 Lbs.	292 mm x 290 mm x 125 mm 11.50" x 11.42" x 4.92"	25 mm 0.98"	5-7 Bar 80-100 PSI	16 kN (3,597 Lbf)	5.0 mm (3/16), 5.0 mm (3/16 M) Monobolt, 6.4 mm (1/4), 6.4 mm (1/4 M) Monobolt

Contact Applifast

Tel: 204 837 8361 • 1 800 563 1293

info@applifast.com

applifast.com