



## Two-Piece HuckBolts®



### BobTail®

Huck's swaged-on fastener with no break-off pintail. Corrosion resistant and installs with lightweight ergonomic tooling.

1/4" - 3/8", 1/2" - 1" and 12mm - 20mm

Steel, Aluminum, Stainless

Grade 2, Grade 5 (Class 8.8),  
Grade 8 (Class 10.9)



### C50L®

Superior vibration resistance and durability for heavy-duty applications. Meets or exceeds all ASTM A-325 standards for shear, tensile and fatigue life.

1/2" - 1-3/8"

Steel, Aluminum, Stainless

Grade 5 (Class 8.8), Grade 8 (Class 10.9)



### C6L®/C120L/C150L

The classic 6-groove locking fastener ideal for a wide range of applications. Available in grades 2, 5, and 8.

3/16" - 3/8"

Steel, Aluminum, Stainless,  
Steel Pin with Stainless Head

Grade 2, Grade 5 (Class 8.8),  
Grade 8 (Class 10.9)



### Hucktainer®

Panel fastener that installs with consistent pressure, reducing crushing or crazing.

3/8"

Steel



### Magna-Grip®

Vibration-resistant, reliable grade 2 fasteners offering high uniform installed values with a wide grip range.

3/16" - 3/8"

Steel, Aluminum

# Huck® Structural Blind Fasteners



## Auto-Bulb®

Features a tapered lead-in point for automated, high-speed assemblies. Forms a bulb directly on the sheet line, preventing pull-through. Available in stainless steel.

3/16", 1/4"

Steel, Stainless Steel

Protruding, Countersunk



## BOM®

Blind, Oversize, Mechanically locked fasteners. Unique push-&-pull installation design for ultimate locking strength from blind-side install.

3/16" – 3/4"

Steel



## FloorTight®

Self-countersinking design for consistent installations in plywood and plymetal vehicle floor applications.

1/4", 5/16"

Steel

Standard, Wide Flange, Plymetal, 90° Countersunk



## HuckLok®

Wide 1/4" grip range, double-locking action clamps assembly from both sides for maximum joint integrity.

3/16", 1/4"

Steel

Protruding, Truss, 100° Oval Countersunk



## Magna-Bulb®

Unique bulbing fastener with high shear strength offers a broader bearing surface for high pull-out strength in thin materials and/or oversized holes.

3/16", 1/4", 5/16"

Steel

Protruding, Truss, 100° Oval Countersunk



## Magna-Lok®

Hole-filling fastener with excellent gap pull-out and moisture resistance. Solid circle lock creates internal lock that virtually eliminates pin push-out. Now available in 1/2" and 3/16" Stainless Steel.

3/16", 1/4", 3/8", 1/2"

Steel, Aluminum, Stainless Steel, 316 Stainless Steel

Protruding, Truss, 100° Flush



## Magna-Tite®

Has water-resistant sealant, for oversize holes and repairs. Large blind-side footprint for use in thin or low-strength materials.

3/16", 1/4"

Aluminum

Protruding, Shavable, Low Profile, 100° Oval Countersunk

# Applifast.



251 Cree Crescent, Winnipeg, MB Canada R3J 3X4  
Tel: 204 837 8361 • 1 800 563 1293  
info@applifast.com



[applifast.com](http://applifast.com)