



GAUGE TO THICKNESS

Gauge		Stainless	Galvanized	Sheet Steel	Aluminum	Wire
	Fraction	Inches (mm)	Inches (mm)	Inches (mm)	Inches (mm)	Inches (mm)
30		0.0125 (0.33)	0.0157 (0.40)	0.0120 (0.30)	0.0100 (0.25)	0.1285 (3.26)
29		0.0141 (0.36)	0.0172 (0.44)	0.0135 (0.34)	0.0113 (0.29)	0.1360 (3.45)
28	1/64	0.0156 (0.41)	0.0187 (0.47)	0.0149 (0.38)	0.0126 (0.32)	0.1405 (3.57)
27		0.0172 (0.43)	0.0202 (0.51)	0.0164 (0.42)	0.0142 (0.36)	0.1440 (3.66)
26		0.0187 (0.48)	0.0217 (0.55)	0.0179 (0.45)	0.0159 (.40)	0.1470 (3.73)
25		0.0219 (0.56)	0.0247 (0.63)	0.0209 (0.53)	0.0179 (0.46)	0.1495 (3.80)
24		0.250 (0.64)	0.0276 (0.70)	0.0239 (0.61)	0.0201 (0.51)	0.1520 (3.86)
23		0.0281 (0.71)	0.0306 (0.78)	0.0269 (0.68)	0.0226 (0.58)	0.1530 (3.91)
22	1/32	0.0312 (0.79)	0.0336 (0.85)	0.0299 (0.76)	0.0253 (0.64)	0.1570 (3.99)
21		0.0344 (0.86)	0.0366 (0.93)	0.0329 (0.84)	0.0285 (0.71)	0.1590 (4.04)
20		0.0375 (0.95)	0.0396 (1.01)	0.0359 (0.91)	0.0320 (0.81)	0.1610 (4.09)
19		0.0427 (1.1)	0.0456 (1.16)	0.0418 (1.06)	0.0359 (0.91)	0.1660 (4.22)
18		0.0500 (1.27)	0.0516 (1.31)	0.0478 (1.21)	0.0403 (1.02)	0.1695 (4.31)
17		0.0562 (1.4)	0.0575 (1.46)	0.0538 (1.37)	0.0453 (1.1)	0.1730 (4.40)
16	1/16	0.0625 (1.59)	0.0635 (1.61)	0.0598 (1.52)	0.0508 (1.29)	0.1770 (4.50)
15		0.0703 (1.8)	0.0710 (1.80)	0.0673 (1.71)	0.0571 (1.4)	0.1800 (4.57)
14	5/64	0.0781 (1.98)	0.0785 (1.99)	0.0747 (1.90)	0.0641 (1.63)	0.1820 (4.62)
13	3/32	0.094 (2.4)	0.0934 (2.37)	0.0897 (2.28)	0.072 (1.8)	0.1850 (4.70)
12	7/64	0.1094 (2.78)	0.1084 (2.75)	0.1046 (2.66)	0.0808 (2.05)	0.1890 (4.80)
11	1/8	0.1250 (3.18)	0.1233 (3.13)	0.1196 (3.04)	0.0907 (2.30)	0.1910 (4.85)
10	9/64	0.1406 (3.57)	0.1382 (3.51)	0.1345 (3.42)	0.1019 (2.59)	0.1935 (4.92)
9	5/32	0.1563 (3.97)	0.1532 (3.89)	0.1495 (3.80)	0.1144 (2.91)	0.1960 (4.98)
8	11/64	0.1719 (4.37)	0.1681 (4.27)	0.1644 (4.18)	0.1285 (3.26)	0.1990 (5.06)
7	3/16	0.1875 (4.76)	N/A	0.1793 (4.55)	0.1443 (3.67)	0.2010 (5.10)
6	13/64	0.2031	N/A	0.1943 (4.94)	0.162 (4.1)	0.2040 (5.18)
5	7/32	0.2187	N/A	0.2092 (5.31)	0.1819	0.2055 (5.22)
4	15/64	0.2344	N/A	0.2242 (5.69)	0.2043	0.2090 (5.34)
3	1/4	0.25	N/A	0.2391 (6.07)	0.2294	0.2130 (5.41)