

NOTE:
 (B) 1. THE FOLLOWING STEEL DFLECTORS ARE OPTIONALLY AVAILABLE:
 FOR USE WITH 246 TOOL, USE 123634-246.
 FOR USE WITH 2502/2503 TOOL USE 123634-2503.
 FOR USE WITH 2580 TOOL USE 123634-2580.

REV	DESCRIPTION	DATE
B	ADDED NOTE: 1	10/31/00

FORM KE104 - REV. C		By accepting this proprietary Huck drawing, recipient agrees not to reproduce or disclose any part thereof to any others without the written permission of Huck International, Inc.	
MATERIAL:	SPEC:	TOLERANCES UNLESS OTHERWISE SPECIFIED:	HUCK INTERNATIONAL, INC., I.S.D. 85 GRAND STREET, P.O. BOX 2270 KINGSTON, NEW YORK 12401
HARDNESS:	(RAW OR STOCKED STATE)	(ALL DIMENSIONS ARE IN INCHES)	
HEAT TREAT TO:	SPEC:	.XX, .XXX ±	NOSE ASSEMBLY -08 FLOOR FASTENER
SURFACE TREAT:	SPEC:	INT. COR. RADII	
SURFACE FINISH NOT TO EXCEED:	Ra	BREAK EDGES	DET: SMR CK:
IDENTIFICATION PER SPEC 42-31:	★ ETCH	ANGLES ±	DATE: 07/16/96 SCALE: 2/1
SURFACES TO BE	☉, //, ⊕, ⊥, & ☐ WITHIN T.I.R.	FINAL ASSY:	FOC: FAC: B 99-3441

Contact Applifast

Tel 204 837 8361 • 1 800 563 1293

info@applifast.com

applifast.com