Applifast.



Multi-Functional



Pneudraulic Blind Riveting Tools

AirPower Series pneudraulic blind riveting tools from Applifast are distinguished from other riveters by a streamlined, ergonomic design allowing easy set up and are constructed for continuous reliable use in demanding production conditions.

- ✓ Durable
- ✓ User-Friendly
- Ergonomic
- ✓ High-Speed
- ✓ Multi-Functional
- Cost Efficient

Experience the efficiency of AirPower riveting

✓ The **multi-functional trigger** has low action for hours of comfortable use with one or two fingers.

✓ The integral mandrel collection system holds the rivet in the nose piece even when working 'face-down'.

✓ A **360° revolving air inlet** accommodates right or left handed users and can be rotated to access tight fastening locations in any position.

✓ A composite body reduces the weight of the tool and also prevents scratching to assembly materials.




applifast.com

251 Cree Crescent Winnipeg, MB R3J 3X4 Canada Unit 5 - 1249 Seagrave Road Woodstock, ON N4T 0A8 Canada Tel: 1 800 563 1293 info@applifast.com

Applifast.

Tooling





Pneudraulic Blind Riveting Tools

* PRN nose tips are available in 1/8", 3/16" and extended 1/8".

Multi-functional trigger controls the suction. When the trigger is pressed and shifted up, the suction is deactivated, when pressed and shifted down the suction is activated.

> Designed with ergonomics in mind to increase endurance and personal comfort on the production line.

Composite body to eliminate scratching and marring of material surfaces. Tool suction holds a rivet in the tool while positioning even in face-down applications.

> Tool hanger allows the riveter to be suspended from a tool balancer.

AP3 Z-13026001

120

360° rotating air inlet enables a right handed or left handed operator to rivet in any position.

Articulating swivel air hose saves air consumption with inline shut-off slide valve.

Multi-functional mandrel collector is a simple and effective system for maintaining a safe and tidy production area.

	ALC: NO							
Model	Model Capacity		Weight	Dimensions	Stroke	Pressure Required	Traction power (6 bar)	Nose Pieces Included
AirPower 1 Z-1100001	2.4 - 4.8 mm 3/32" - 3/16"	Al, St, Rv Al, St, Rv	1.447 Kg 3.191 Lbs.	272 mm x 264 mm x 99 mm 10.71" x 10.39" x 3.90"	17 mm 0.67″	5-7 Bar 80-100 PSI	7.3 kN (1,641 Lbf)	3.0 mm (1/8), 4.0 mm (5/32), 5.0 mm (3/16)
AirPower 2 Z-1200001	4.0 - 6.4 mm 5/32" - 1/4"	Al, St, Rv Al, St, Rv	1.848 Kg 4.075 Lbs.	272 mm x 275 mm x 120 mm 10.71" x 10.83" x 4.72"	21 mm 0.83″	5-7 Bar 80-100 PSI	12.5 kN (2,810 Lbf)	4.0 mm (5/32), 4.8/5.0 mm (3/16), 6.0 mm/6.4 mm (1/4)
AirPower 3 Z-13026001	4.8 - 6.4 mm 3/16" - 1/4"	Al, St, Rv Al, St, Rv	2.019 Kg 4.451 Lbs.	292 mm x 290 mm x 125 mm 11.50" x 11.42" x 4.92"	25 mm 0.98"	5-7 Bar 80-100 PSI	16 kN (3,597Lbf)	5.0 mm (3/16), 5.0 mm (3/16 M) Monobolt, 6.4 mm (1/4), 6.4 mm (1/4 M) Monobolt

251 Cree Crescent Winnipeg, MB R3J 3X4 Canada Unit 5 - 1249 Seagrave Road Woodstock, ON N4T 0A8 Canada Tel: 1 800 563 1293 info@applifast.com





applifast.com